

R S L

Refreshment Systems Ltd.

Cleaning Guide La Spaziale s5



Contact us

www.refreshmentsystems.co.uk

For Service:
service@refreshmentsystems.co.uk
01274 750 008

For Ingredients:
ingredients@refreshmentsystems.co.uk
01226 720 482

This cleaning guide is for **advice only**

Please refer to the operative manual for complete safety information and instruction when considering any maintenance on the machine.



espresso coffee machines

CLEANING ROUTINE

In order for the machine to produce good coffee consistently, the following should be carried out.

**CARE SHOULD BE TAKEN TO AVOID BURNS –
THE MACHINE MAY BE HOT!!!**

DURING SERVICE

- The Steam Wand **must** be wiped after **every usage**.
- The Steam Wand **must** be opened to clear of milk after **every usage**.
- The group head **should be brushed** with the wire **brush provided** after busy periods to clear any coffee debris.

DAILY AT END OF SERVICE

- Be sure the Steam Wand is wiped perfectly clean.
- Be sure the holes in the steam wand are clear.
- Clean the shower heads below the brewing groups with the wire brush provided.
- Clean the filter holders making sure that it is clean **under the coffee baskets**.
- Using the blanking disc provided, **Back-Flush** the machine with **Ascor Cleaning Powder**:-
 1. Place the **Blank Disc** in the **Double Filter Holder**
 2. Place a small (.25 tsp) Ascor in the **Double Filter Holder filter basket**
 3. Secure the filter holder in the coffee machine.
 4. Press the **free-flow** or **Star Button** and leave to run for 5 seconds.
 5. **Without removing** the group handle, repeat point '4'.
 6. Remove group handle & rinse.
 7. Repeat '3' & '4' **without Ascor Cleaning Powder**
 8. Remove Filter Holder & rinse including group head.
 9. **Repeat for all other group heads.**
- Rinse & wipe the drip tray.
- Wipe surfaces with a soft cloth.

WEEKLY

- Turn **OFF** the machine & using the **Tool Provided**, remove the shower plates taking care to notice the order of removal. **THESE CAN BE HOT!! BEWARE**
- Clean them carefully soaking overnight if necessary to ensure all the holes are clear.

- Reassemble in the same order as removal being careful - **DO NOT OVERTIGHTEN!!!**